

500 Carpet Seam Sealer

DESCRIPTION

Polymer 500 is an extrudable solvent based neoprene contact type adhesive. This adhesive has good water and heat resistance.

FOR BONDING

Carpet seam edges together where carpet is either directly bonded to the floor or double bonded over underlay.

STANDARDS

Australian/NZ Standard 2455.1-1995 "Textile Floor Coverings Installation Practice"

APPLICATION

Apply a 3mm bead Polymer 500 to the subfloor or double-bond underlay. Lay carpet seams into wet bead of adhesive.

CLEAN UP

Polymer Clean No. 2 for equipment and tools. Use extreme care when using Clean No. 2 on carpet, vinyl, etc.

TECHNICAL DATA

Appearance	Honey like
Base	Neoprene rubber
Solids	22% (approx)
Carrier	Hydrocarbon solvent
Flammability	Flammable
Viscosity	1,800 Cps (approx)
Toxicity	Toxic
S.G.	0.90 (approx)

SHELF LIFE

12 months under good storage conditions in original unopened containers stored out of direct sunlight, under cover and away from all sources of heat and ignition.

SAFETY & HANDLING

Polymer 500 Seam Sealer adhesive is a flammable product. Good housekeeping and ventilation is essential. Do not smoke whilst using and do not use near heat sources or open flames. For further information refer to Material Safety Date Sheet.

HEALTH HAZARD & FIRST AID

400 Seam Sealer adhesive is a flammable product. Good housekeeping and ventilation is essential.

Avoid skin contact. Use in well ventilated areas. Keep away from ignition sources, sparks, flames. Do not smoke when using.

For further information refer to Material Safety Data Sheet. If poisoning occurs, contact a doctor or the Poisons Information Centre. If swallowed, **DO NOT** induce vomiting. Give a glass of water.

STORAGE

This product is classified:

UN 1133
D.G. Class 3
Hazchem 3 YE
Packaging Group II

and is **HIGHLY FLAMMABLE**. This product should be stored accordingly and in line with correct regulations.

Warning: Intentional misuse by deliberately inhaling vapours can be harmful or fatal.

Issued: May 2007

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

POLYMER ENGINEERING Australia ACN 004 709 915
A Division of RLA Polymers Pty Ltd
215 Colchester Road, Kilsyth Victoria 3137 Australia
Telephone 03 9761 5331 Facsimile 03 9728 6009



POLYMER ENGINEERING New Zealand
67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand
Tel: (9) 268 0301 Fax: (9) 268 0305