

R101S CONTACT ADHESIVE

PRODUCT DESCRIPTION

Roberts 101S Contact Adhesive is a high quality brushable grade solvent based (flammable), rapid drying contact cement, which has high strength, excellent ageing and heat resistance. Roberts 101S Contact Adhesive is designed for use on most types of vinyls, PVC skirtings/extrusions, coverstrips, plastic and metal treads and nosings, etc. Not recommended for exterior application.

FOR BONDING

Vinyl and PVC skirtings and extrusions, coverstrips, plastic and metal treads nosings, decorative Laminates, MDF, wood and wood Veneer, paper honeycomb to steel, timber, concrete, plasterboard and most common building substrates. This adhesive has good heat resistance but like all similar adhesives can be adversely affected by plasticiser migration from PVC products.

SURFACE PREPARATION

Surface to be bonded must be clean, dry and free from oil, dust, loose paint and other contaminants that may affect adhesion. Highly porous substrates may require a prime coat prior to the main coat.

APPLICATION

Apply adhesive liberally with brush, roller or notched trowel. Both bonding surfaces must be coated evenly and allowed to dry until 'touch dry'. This will take a minimum of 5-10 minutes at 20°C. They should be joined within 30 minutes of application.

CLEAN UP

To clean up equipment and adhesive spills, use Roberts 900 Contact Cleaner (flammable). Roberts 900 is not recommended for removing adhesive from carpet, vinyl or lacquered surfaces.

STORAGE/ HANDLING

Keep container tightly closed. Store Locked up.
Keep container in a cool well ventilated place away from sources of heat.
A Safety Data Sheet Available on request

PACKAGING

1, 4 and 20 litre

COVERAGE

Up to 5-7m² per litre

TYPICAL PROPERTIES

Appearance: Pale yellow

Base: Neoprene Synthetic Rubber

Solids: Approx 22%

Viscosity: Thin liquid

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilisyth, Victoria 3137 Australia

P.O. Box 147, Kilisyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



**adhesives hot melts tapes
levelling powders primers**





PRODUCT
DATA

SHELF LIFE

12-14 months in unopened containers stored out of direct sunlight

SAFETY DIRECTIONS

KEEP away from HEAT/SPARKS/OPEN FALMES/HOT SURAFCES – NO SMOKING

Keep container tightly closed . Keep container in a cool well ventilated place.

Use only non-sparking tools

During the installation process , adequate ventilation of the work area should be maintained without causing the entry of contaminants to other parts of the building.

In case if insufficient ventilation wear suitable respiratory equipment. Wear protective gloves, eye and face protection.

Use Personal Protective Equipment as required. Take precautionary measures against static discharges. Wash thoroughly after handling. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid Eyes and Skin contact .IF ON SKIN Remove immediately all contaminated clothing and rinse skin with water. IF ON SKIN wash with plenty of soap and water .If skin irritation occurs get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF IN EYES Rinse carefully with water for several minutes. If eye irritation persists get medical advice/attention. If exposed or concerned get medical advice/attention

Person who are sensitive to odours and or chemicals should avoid the work area.

IN case of FIRE use foam to extinguish.

Safety Data Sheet Available on request

FIRST AID

For advice contact a Poison Information Centre (Australia PH: 13 11 26 , New Zealand PH: 0800 764 766) or a doctor at once.If Swallowed do NOT induce vomiting , If inhaled , remove from contaminated area.

In case of accident or if you feel unwell contact a doctor or Poison information centre.

IF IN EYES Rinse carefully with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists get medical advice/attention.

adhesives hot melts tapes
levelling powders primers

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



Warranty Statement

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that when fully cured this product is suitable for use and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace product free of charge when purchased from any legally verifiable source, and where product is proven to have been stored, handled and installed according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with the relevant Australian Standard and the Floorcovering Manufacturers instructions and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't not apply if damage, loss, failure to follow instructions or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

Phone: 1800 242 931

Email: info@rlapolymers.com.au

Mail: 215 Colchester Road Kilsyth Victoria 3137 (attn Customer Services)

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage.

You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests.

Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: July 2016

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facs/mile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlagroup.com.au



adhesives hot melts tapes
levelling powders primers

