

5601 Vinyl Seam Adhesive

Roberts 5601 Vinyl Seam Adhesive is a specifically formulated flammable solution for chemically welding vinyl sheet flooring seam.

Not recommended for vinyl sheet flooring with a urethane wear surface.

Surface Preparation

Seams must be dry and free of adhesive. Wipe the seam area with a clean cloth dampened with water. Allow area to dry before applying Roberts 5601 Vinyl Seam Sealer.

Application

To be used with an applicator bottle.

Do not shake Roberts 5601 Vinyl Seam Sealer within half an hour before using to avoid air bubbles.

Transfer Roberts 5601 Vinyl Seam Sealer to applicator bottle and reseal container tightly. Starting at one end of the seam, insert the applicator tip into the seam and apply a continuous bead along the entire length of the seam. Avoid excessive downward pressure and maintain continuous pressure to the applicator bottle during the sealing process.

Typical Properties

Appearance	Clear liquid
Base	Synthetic resins
Solids	21% (approx)
Viscosity	Thin syrup
Flash point	Less than 0°C
Shelf life	Up to 6 months in sealed container at 20°C
Packaging	250ml
Contains	850ml/litre Ketones (approx)
Coverage	Approx 125lm per 250ml

Caution – Highly Flammable

Contains Flammable Solvents – Use in a ventilated area away from flame or sparks. Store in a tightly sealed container in a cool, dry place.

Highly Flammable

Avoid contact with skin and eyes and avoid breathing vapour

First Aid

If poisoning occurs, contact a doctor or the Poisons Information Centre.

If swallowed, **DO NOT** induce vomiting. Give a glass of water.

Safety Directions

Storage and use of this product is controlled by Local, State and Commonwealth Government Regulations.

Store in a well ventilated area away from oxidising agents.

In use, please ensure that Occupational Health and Safety requirements are observed. Work areas should be well ventilated and free of ignition sources. Prolonged skin contact or inhalation of vapours is advised against.

Safety & Handling

A Material Safety Data Sheet is available on request.

Issued: May 2007

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Roberts Australia ACN 004 709 915
a division of RLA Polymers Pty Ltd
215 Colchester Road, Kilsyth, Victoria 3137, Australia
Tel: (03) 9728 1605 Fax: (03) 9728 6009



Roberts New Zealand
67 Dalgety Drive (P.O. Box 97-575)
Manukau City, Auckland, New Zealand
Tel: (9) 268 0301 Fax: (9) 268 0305

adhesives
tapes
melting
hot
powders
levelling