



CAPITOL PRO PRIMER

Primer for use with Capitol Levelling Compounds

Use for smooth, dense, and non porous substrates

Can be used diluted or undiluted

Up to 10m² on porous substrates

Australian Flooring Supplies

68 Prosperity Way
Dandenong South VIC 3185

Phone: 1300 737 155

www.shopqep.com.au

CAPITOL PRO PRIMER

Primer for use with Capitol Levelling Compounds

PRODUCT DESCRIPTION

Capitol Pro Primer is a specialised internal water - based primer compatible with Capitol floor levelling compounds and approved Capitol waterproofing membranes to smooth dense and various non porous substrates and is suitable for internal and external wall & floor applications.

SUBSTRATES (FLOOR LEVELLERS)

Internal particleboard, plywood, compressed fibre-cement sheets, concrete, masonry and lightweight concrete blocks, Autoclave Aerated Concrete (AAC), existing glazed tiles (Tiles to be deglazed before priming).

Note: Not suitable for steel trowelled finish concrete where Capitol floor levellers are being installed.

SUBSTRATE PREPARATION

All substrates must be clean, sound and free from dust, release agents, and other contaminants. Ensure surfaces are dry with no residue or permanent damp.

APPLICATION

Apply using a bristle broom, apply at a rate of 6 - 10m² per litre over the surface. For floor levelling compounds and absorbent substrates, dilute Capitol Pro Primer with water 1:1 by volume. All tools should be cleaned with water immediately after use.

DRYING TIME

Ensure Capitol Pro Primer is fully dry prior to application of subsequent products, allow approx 20 minutes at 23°C and 50% relative humidity. Drying times will be affected by porosity of substrate and climatic conditions. Allow longer for lower temperatures or high relative humidity.

COVERAGE

Capitol Pro Primer 4L will cover 24 - 40m². Coverage is dependent on the porosity of the surface and method of application.

SHELF LIFE & STORAGE

Capitol Pro Primer has a shelf life of 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

Do not return excess primer back to original packaging as this may cause contamination. Do not use in negative hydrostatic pressure situations. Replace lid

after use and store away from direct sunlight.

SAFETY PRECAUTIONS

This product may cause an allergic skin reaction and may cause respiratory irritation. May cause cancer and may cause damage to the unborn child. This product is harmful to aquatic life with long lasting effects. In case of contact with the eyes, rinse with running water until advised to stop by the Poisons Information centre or a doctor, or for at least 15 minutes. Ensure adequate ventilation during mixing and application. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell.

Additional information is in the Safety data sheet SDS at www.shopQEP.com.au

Australian Flooring Supplies
68 Prosperity Way
Dandenong South VIC 3185
Phone: 1300 737 155
www.shopqep.com.au

June 2023